

Applicants: Raymond A. Wekluk  
Serial No. : 10/808,708  
Filed : March 18, 2004  
Page : 8 of 9

Attorney Docket No.: Navy Case 84966

### REMARKS

By this Amendment, and claims 1-20 are amended to recite features supported in the specification at, for example, page 3, line 8 – page 5, line 11 (corresponding to paragraphs [0007] – [0010] in U.S. Patent Application Publication 2005/0204833) and FIG. 1. Accordingly, claims 1-20 are pending in this application. No new matter is added by any of these amendments.

Reconsideration based on the following remarks is respectfully requested.

The Office Action rejects claims 1-20 as being allegedly indefinite under 35 U.S.C. §112, second paragraph. This rejection is respectfully traversed.

The claims are amended to obviate the rejection and to improve clarity from antecedence ambiguities.

Applicant's claims are directed generally, for example, an adjustable mounting device (10) to retain a proximity sensor (70) for locating a target element (74). The device includes, *inter alia*, a base (12), a C-shaped member (20) and a mounting plate (43). The base (12) includes a bottom (14) flanked by opposed orthogonal sides (16, 18). The C-shaped member (20) includes a bottom leg (22) disposed between the orthogonal sides (16, 18), a vertical leg (24) supported by the bottom leg (22) and a top leg (26) supported by the vertical leg (24). The mounting plate (43) includes a threaded aperture (58) having threads (60) to receive and retain the sensor (70).

A pair of guide dowels (28, 30) extend from one of the opposed orthogonal sides (16) through the bottom leg (22) and to the other of the opposed orthogonal sides (18). A threaded bolt (36) is disposed between and substantially parallel to the dowels (28, 30). The threaded bolt (36) extends from counter bored apertures (40) in the opposed orthogonal sides (16, 18) through a threaded aperture (38) in the bottom leg (22).

A third guide dowel (50), disposed substantially perpendicular to the pair (28, 30), extends from the top leg (26) through the mounting plate (43) and to the bottom leg (22). A threaded bolt (44) is disposed substantially parallel to the third dowel (50). The threaded bolt

Applicants: Raymond A. Wekluk  
Serial No. : 10/808,708  
Filed : March 18, 2004  
Page : 9 of 9

Attorney Docket No.: Navy Case 84966

(44) extends from counter bored apertures (45) in the top and bottom legs (26, 22) through a threaded aperture (46) in the mounting plate (43).


The threaded aperture (58) in the mounting plate (43) provides a mechanism to retain the sensor (70) for locating the target element (74). The sensor (70) includes threads (72) that engage the threads (60) of the aperture (58) in the mounting plate (43).

Consequently, all the claims are in condition for allowance. Applicant respectfully requests that the rejection under 35 U.S.C. §112, second paragraph, be withdrawn.

In view of the foregoing amendments and remarks, Applicant respectfully submits that this application is in condition for allowance. Favorable reconsideration and prompt allowance are earnestly solicited.

Should the Examiner believe that anything further is desirable in order to place this application in even better condition for allowance, the Examiner is invited to contact Applicant's undersigned representative at the telephone number listed below.

Respectfully submitted,



Gerhard W. Thielman  
Registration No. 43,186

Date: February 6, 2006

DEPARTMENT OF THE NAVY  
Naval Surface Warfare Center – Dahlgren Division  
Office of Counsel – Code XDC1  
17320 Dahlgren Road  
Dahlgren, Virginia 22448-5100  
Telephone: (540) 653-8061 Customer No. 23501

DEPOSIT ACCOUNT USE  
AUTHORIZATION

Please grant any extension  
necessary for entry;

Charge any fee due to our  
Deposit Account No. 50-0967